

DEF SERIES

HOT WATER PRESSURE WASHER

Direct Drive • Electric Powered • Fuel Oil Heated

- **Downstream Adjustable Chemical Injector:**
For low pressure soap and chemical injection.
- **Quick Connect Hose Connectors:**
For easy on/off connections
And tangle free hoses.
- **Heavy Duty Steel Frame:**
Includes handle, hose holder
and a powder coated epoxy
finish.
- **Large Burner Temperature Dial:**
Adjust water temperature
with ease.
- **Easy Access On/Off Toggle Switch:**
Includes indicator light.
- **Replaceable Fuse:**
For electronic overload
protection.
- **Easy Access Control Panel:**
Makes servicing your machine
fast and easy.

- **Powder Coated Coil Skin:**
Schedule 80 heating coil and 172,000
BTU burner.



- **10" Pneumatic Tires:**
Ball bearing construction with a
steel rim and hub assembly.

- **Four Quick Connect Nozzles:**
Colour coded nozzles included
are 0°, 15°, 25° and soap QC.
- **50' High Pressure Hose:**
Durable non-marking steel
braided hose.
- **Quality Gun and Lance Combination:**
Easy pull trigger with 48" lance.
- **Separate Unloader:**
Diverts water pressure when
trigger is not in use. Includes
easily adjustable pressure
control knob and all brass
fittings.
- **High Quality Triplex Plunger Pump:**
All Dynablast pressure
washers include GP/Interpump
pumps with solid ceramic
plungers, thermal pump
protector and limited 5 year
warranty.
- **Large Fuel Oil Tank:**
Hold up to 4.4 gallons of No.1
or 2 Fuel Oil. Also includes a
fuel indicator gauge.

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	H2015DEF1
Operating Pressure (PSI):	1500
Volume (GPM):	2.0
Motor (HP):	2
Available Voltage (1 Phase):	115
Amps:	20
Pump Speed:	3450
BTU:	172,000
Time Delay Shutdown:	NO
Unit Dimensions (LxWxH):	42"x26"x40"
Unit Weight:	290 lbs

Features and specifications subject to change without prior notice.

Other Features:

- **High Pressure Blow Off Valve:**
For added safety.
- **Baldor Electric ODP Motor**
- **Heavy Duty Power Cord**
- **12v Beckett Burner:**
No external electricity
required.



Distributed by:

Dynablast®



DEF-H2105-02/07

www.dynablast.com